

AF32 Series Automatic Faucet



	AF320	AF321
Material	Chrome Plated Cast Brass	Chrome Plated Cast Brass
Dimensions (W x H)	50mm x 178mm	50mm x 185mm
Packaging	6 sets/carton	6 sets/carton
Measurement	1.5 cuft.	1.5 cuft.
Gross weight	12.2kgs (26.9lbs)	13.4kgs (29.5lbs)
Ceramic Bore Diameter	Single-Hole Lavatory or Deck (28Φ~45Φ)	Single-Hole Lavatory or Deck (35Φ~45Φ)
Power Supply	AC Adapter or AA type battery x 4	AC Adapter or AA type battery x 4
Battery Life	3 years (3,000 cycles per month)	3 years (3,000 cycles per month)
Low Battery Indicator Light (LED)	Available	Available
Operating Voltage	110V-220Vac, 50/60 Hz, 5W	110V-220Vac, 50/60 Hz, 5W
Standby Power	0.3W	0.3W
Sensing Range	15cm	15cm
Shut-off Delay Time	1 sec	1 sec
Time out Setting (facing up)	N/A	N/A
Time out Setting (facing down)	1 minute	1 minute
Operating Water Pressure	10 to 100 PSI	10 to 100 PSI
Water Supply Connection	PF 1/2	PF 1/2
Applicable Water Temperature	39°F~185°F (4°C ~ 85°C)	39°F~185°F (4°C ~ 85°C)



AF32 Series Automatic Faucet



double sensors

AF322 AC **AF320 DC**

All-In-One
Faucet With **Hot and Cold Water** Supply




double sensors

AF323 AC **AF323 DC**

All-In-One
Faucet With **Single Water Line** Supply



	AF322	AF323
Material	Chrome Plated Cast Brass	Chrome Plated Cast Brass
Dimensions (W x H)	50mm x 185mm	50mm x 178mm
Packaging	6 sets/carton	6 sets/carton
Measurement	1.5 cuft.	1.5 cuft.
Gross weight	14.6kgs (32.2lbs)	12.2kgs (26.9lbs)
Ceramic Bore Diameter	Single-Hole Lavatory or Deck (35Φ~45Φ)	Single-Hole Lavatory or Deck (28Φ~45Φ)
Power Supply	AC Adapter or AA type battery x 4	AC Adapter or AA type battery x 4
Battery Life	3 years (3,000 cycles per month)	3 years (3,000 cycles per month)
Low Battery Indicator Light (LED)	Available	Available
Operating Voltage	110V-220Vac, 50/60 Hz, 5W	110V-220Vac, 50/60 Hz, 5W
Standby Power	0.3W	0.3W
Sensing Range	Auto Adjusted Sensor	Auto Adjusted Sensor
Shut-off Delay Time	1 sec	1 sec
Time out Setting (facing up)	3 minutes	3 minutes
Time out Setting (facing down)	1 minute	1 minute
Operating Water Pressure	10 to 100 PSI	10 to 100 PSI
Water Supply Connection	PF 1/2	PF 1/2
Applicable Water Temperature	39°F~185°F (4°C ~ 85°C)	39°F~185°F (4°C ~ 85°C)

