

AF33 Series Automatic Faucet



AF330 DC

All-In-One

Wall Mounted Automatic Faucet



AF332 DC



All-In-One

Wall Mounted Automatic Faucet

| | AF330 | AF332 |
|--|---------------------------------------|---------------------------------------|
| Material | Chrome Plated Cast Brass | Chrome Plated Cast Brass |
| Dimensions (W x H) | 50mm x 255mm | 50mm x 255mm |
| Packaging | 6 sets/ carton | 6 sets/ carton |
| Measurement | 1.5 cuft. | 1.5 cuft. |
| Gross weight | 16.2kgs (35.7lbs) | 16.2kgs (35.7lbs) |
| Power Supply | AA type x 4 | AA type x 4 |
| Battery Life | 3 years (3,000 cycles per month) | 3 years (3,000 cycles per month) |
| Low Battery Indicator Light (LED) | Available | Available |
| Operating Voltage | 110V-220Vac, 50/60 Hz, 3W | 110V-220Vac, 50/60 Hz, 3W |
| Panel hole | Φ35 | Φ35 |
| Panel thickness | 5~20mm | 5~20mm |
| Time out Setting (facing up) | N/A | 3 minutes |
| Time out Setting (facing down) | 1 minute | 1 minute |
| Standby Power | 0.3W | 0.3W |
| Sensing Range | 10cm (optional: auto adjusted sensor) | 10cm (optional: auto adjusted sensor) |
| Shut-off Delay Time | 1 sec | 1 sec |
| Flow Rate | 2.2GPM/8.3LPM (adjustable) | 2.2GPM/8.3LPM (adjustable) |
| Operating Water Pressure | 10 to 100 PSI | 10 to 100 PSI |
| Water Supply Connection | PF 1/2 | PF 1/2 |
| Applicable Water Temperature | 39°F~185°F (4°C ~ 85°C) | 39°F~185°F (4°C ~ 85°C) |



AF33 Series Automatic Faucet



AF336 DC

AF336 AC

All-In-One

Panel Mounted Automatic Faucet

| AF336 | |
|--|---------------------------------------|
| Material | Chrome Plated Cast Brass |
| Dimensions (W x H) | 50mm x 255mm |
| Packaging | 6 sets/ carton |
| Measurement | 1.5 cuft. |
| Gross weight | 11.6kgs (25.5lbs) |
| Power Supply | AA type x 4 or AC type |
| Battery Life | 3 years (3,000 cycles per month) |
| Low Battery Indicator Light (LED) | Available |
| Operating Voltage | 110V-220Vac, 50/60 Hz, 3W |
| Panel hole | Φ35 |
| Panel thickness | 5~20mm |
| Time out Setting (facing up) | N/A |
| Time out Setting (facing down) | 1 minute |
| Standby Power | 0.3W |
| Sensing Range | 10cm (optional: auto adjusted sensor) |
| Shut-off Delay Time | 1 sec |
| Flow Rate | 2.2GPM/8.3LPM (adjustable) |
| Operating Water Pressure | 10 to 100 PSI |
| Water Supply Connection | PF 1/2 |
| Applicable Water Temperature | 39°F~185°F (4°C ~ 85°C) |

