EcoSwift Hand Dryer

The smallest hand dryer in the market. It takes years of experiences to make a hand dryer the size of one's palm. Universal Design and ADA-Compliant (Americans with Disabilities Act), it fits in every washroom, especially those with restricted spaces such as on trains and airplanes.

HIGH SPEED RANGE

Why EcoSwift?

Specs

- air speed 65-92 m/s
- standby power 0.3-0.4W
- 1.0kW only
- IP24
- carbon filter assembly (optional)

Design

- about the size of A4 paper
- less than 4" from the wall
- heater on/off
- sound & power adjustment
- fewer materials save resource
- recycled and reused

In Use

- 10-15 seconds drying time
- save 80% of energy cost
- three safety protections
- 60s timing protection
- easy to clean
- easy maintenance

Specification



Model Name: EcoSwift01
Cover Finish: White Powder Coating
Cover Material: Stainless Steel (#430)
Operation: Automatic



Model Name: EcoSwift01B
Cover Finish: Matte Black Powder Coating
Cover Material: Stainless Steel (#430)
Operation: Automatic



Model Name: EcoSwift05
Cover Finish: Satin
Cover Material: Stainless Steel (#304)
Operation: Automatic

Specification

Packaging (carton):	4 dryer/carton. G.W. 16.5 kg. Meas. 1.9'
Drying Time:	Less than 15 seconds
Operating Voltage:	110-120 Vac, 50/60 Hz, 7.6-8.4 A, 0.84-1.0 kW 220-240 Vac, 50/60 Hz, 3.8-4.2 A, 0.84-1.0 kW
Motor Wattage:	325-500 W, Adjustable
Standby Power:	0.3-0.4 W
Air Speed:	65-92 m/s, Adjustable
Sound Level:	MIN 68.6 to 72.3 dB(A) MAX @ 1m
Sensing Range:	170 ± 20 mm, Adjustable
Drip Proof:	IP24
Timing Protection:	60 seconds auto shut off
Motor Thermal Protection:	Auto resetting thermostat turns unit off, at 95 °C (203 °F)
Heater Thermal Protection:	Auto resetting thermostat turns unit off at 85 °C (185 °F) Thermal fuse cuts unit off at 142 °C (185 °F)
Safety Approvals:	LVD EMC CE CB UL WEEE RoHS
PVD Color	